



Arnau Albà, PhD student

Start-to-end Modelling of FELs with OPAL-FEL Full Maxwell Solver

OPAL Retreat, June 10th 2021

$$\begin{cases} \vec{\nabla} \cdot \vec{E} = \frac{\rho}{\epsilon_0}, \\ \vec{\nabla} \wedge \vec{E} = -\frac{\partial \vec{B}}{\partial t}, \\ \vec{\nabla} \cdot \vec{B} = 0, \\ \vec{\nabla} \wedge \vec{B} = \mu_0 \vec{j} + \frac{1}{c^2} \frac{\partial \vec{E}}{\partial t}, \end{cases} \Rightarrow \begin{cases} \nabla^2 \phi - \frac{1}{c^2} \frac{\partial^2 \phi}{\partial t^2} = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} - \frac{1}{c^2} \frac{\partial^2 \vec{A}}{\partial t^2} = -\mu_0 \vec{j}. \end{cases}$$

$$\begin{cases} \vec{\nabla} \cdot \vec{E} = \frac{\rho}{\epsilon_0}, \\ \vec{\nabla} \wedge \vec{E} = -\frac{\partial \vec{B}}{\partial t}, \\ \vec{\nabla} \cdot \vec{B} = 0, \\ \vec{\nabla} \wedge \vec{B} = \mu_0 \vec{j} + \frac{1}{c^2} \frac{\partial \vec{E}}{\partial t}, \end{cases}$$

$$\Rightarrow \begin{cases} \nabla^2 \phi - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \phi = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \vec{A} = -\mu_0 \vec{j}. \end{cases}$$

Wave equations for fields

$$\begin{cases} \vec{\nabla} \cdot \vec{E} = \frac{\rho}{\epsilon_0}, \\ \vec{\nabla} \wedge \vec{E} = -\frac{\partial \vec{B}}{\partial t}, \\ \vec{\nabla} \cdot \vec{B} = 0, \\ \vec{\nabla} \wedge \vec{B} = \mu_0 \vec{j} + \frac{1}{c^2} \frac{\partial \vec{E}}{\partial t}, \end{cases} \Rightarrow \begin{cases} \nabla^2 \phi - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \phi = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \vec{A} = -\mu_0 \vec{j}. \end{cases}$$

Wave equations for fields

However, OPAL's FFT solver uses the **electrostatic approximation**:

$$\frac{\partial}{\partial t} \rightarrow 0 \Rightarrow \begin{cases} \nabla^2 \phi = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} = -\mu_0 \vec{j}. \end{cases}$$

$$\begin{cases} \vec{\nabla} \cdot \vec{E} = \frac{\rho}{\epsilon_0}, \\ \vec{\nabla} \wedge \vec{E} = -\frac{\partial \vec{B}}{\partial t}, \\ \vec{\nabla} \cdot \vec{B} = 0, \\ \vec{\nabla} \wedge \vec{B} = \mu_0 \vec{j} + \frac{1}{c^2} \frac{\partial \vec{E}}{\partial t}, \end{cases} \Rightarrow \begin{cases} \nabla^2 \phi - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \phi = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2} \vec{A} = -\mu_0 \vec{j}. \end{cases}$$

Wave equations for fields


However, OPAL's FFT solver uses the **electrostatic approximation**:

$$\frac{\partial}{\partial t} \rightarrow 0 \Rightarrow \begin{cases} \nabla^2 \phi = -\frac{\rho}{\epsilon_0}, \\ \nabla^2 \vec{A} = -\mu_0 \vec{j}. \end{cases}$$

Fields are **not** time dependent.

Electrostatic approximation breaks down in wigglers and undulators because:

- Particles emit radiation
- Wiggly motion means particles in bunch move in different directions
- Wave-particle interaction effects cannot be neglected




Credit: A. Marinelli [1]

Wigglers are used to produce radiation and to shape phase-space in:

- Synchrotrons
- Free Electron Lasers
- Experimental beamlines [2], [3], [4]

Electrostatic approximation breaks down in wigglers and undulators because:

- Particles emit radiation
- Wiggly motion means particles in bunch move in different directions
- Wave-particle interaction effects cannot be neglected



Credit: A. Marinelli [1]


Wigglers are used to produce radiation and to shape phase-space in:

- Synchrotrons
- Free Electron Lasers
- Experimental beamlines [2], [3], [4]


So how do we model undulators?

MITHRA [5], [6] is an open source “Full-Wave Simulation Tool for Free Electron Lasers” developed by Arya Fallahi. It solves the full Maxwell equations in 3D space with an FDTD-PIC scheme, separately **integrating particles and fields**:

MITHRA [5], [6] is an open source “Full-Wave Simulation Tool for Free Electron Lasers” developed by Arya Fallahi. It solves the full Maxwell equations in 3D space with an FDTD-PIC scheme, separately **integrating particles and fields**:




OPAL FFT solver




MITHRA (and OPAL-FEL) full-wave solver

In MITHRA the mesh and fields need to be in a **inertial frame of reference**, so an **adaptive grid is not possible**.

Laboratory frame




Boosted frame



Thus MITHRA can only work as long as the bunch has a constant mean velocity, i.e. it can only simulate the bunch inside the undulator!


By including MITHRA as a solver in OPAL we obtain OPAL-FEL [7], capable of **automatically switching between solvers**, and simulating full beamlines including an undulator!



Install with `cmake -DENABLE_OPAL_FEL=yes ...` (see [manual](#) for details).

The parameters of the `UNDULATOR` element also define the full-wave solver, because the full-wave solver is attached to the element:

```
UND: UNDULATOR, ELEMEDGE = 44.0e-2, K = 10.81, LAMBDA = 8.5e-2,  
NUMPERIODS = 5,  
MESHLENGTH = { 12e-3, 12e-3, 4e-3 }, MESHRESOLUTION = { 1e-5, 1e-5, 8e-6},  
FNAME = "output.job";
```



Output from the full-wave solver depends on output.job:


```

BUNCH
{
  bunch-sampling
  {
    sample      = true
    directory   = ./
    base-name   = bunch-sampling/bunch
    rhythm      = 100e-12
  }
}

FIELD
{
  field-sampling
  {
    sample      = false
    type        = at-point
    field       = Ex
    field       = Ey
    field       = Ez
    directory   = ./
    base-name   = field-sampling/field
    rhythm      = 3.2e-12
    position    = (0.0, 0.0, 110.0e-6)
  }
}

FEL-OUTPUT
{
  radiation-power
  {
    sample      = true
    type        = at-point
    directory   = ./
    base-name   = power-sampling/power
    plane-position = 1.1e-4
  }
}

```



The UNDULATOR element is a drift with a wrapper function

```
void Undulator::apply(
    PartBunchBase<double, 3>* itsBunch,
    CoordinateSystemTrafo const& refToLocalCSTrafo)
```


which

- is called when bunch enters undulator fringe field (in `computeExternalFields(oth)`; for OPAL-t)
- does coordinate transformation on particles before undulator
- initialises fields and mesh
- initialises and runs MITHRA full-wave solver


```
MITHRA::FdTSC solver(mesh, bunch, seed,
    undulators, externalFields, FELs);
solver.solve();
```

- coordinate transformation back to lab frame when bunch exits undulator
- reference particle placed in bunch centroid after full-wave simulation


Full-wave solver **does not** write in the OPAL stat file:





Full-wave solver does not write in the OPAL stat file:






Can be fixed with Lorentz transformation of output from full-wave solver (approximation):



- Reproduce findings and LCLS experiment from paper by MacArthur et al. [3].
- Radiation from high current tail expected to create energy modulation in beam core.




D1: DRIFT, ...
 YAG1: MONITOR, ...
 D2: DRIFT, ...
 UND: UNDULATOR, ...
 D3: DRIFT, ...
 YAG2: MONITOR, ...
 D4: DRIFT, ...





OPAL-FEL for AWA experiment

Whole beamline was modelled to prepare AWA experiment for micro-bunched electron cooling [4], [8], [9].



Whole beamline was modelled to prepare AWA experiment for micro-bunched electron cooling [4], [8], [9].



- OPAL can now successfully model undulators and wigglers
- Can automatically switch between solvers
- Benchmarked and used in experiments
- Uses external MITHRA library \Rightarrow full-wave solver maintained and improved externally

Drawbacks and room for improvement:

- Hacky implementation
 - Full-wave solver cannot write to stat file
 - Solver attached to undulator element only, rather than being a solver class
 - Reference particle does not see undulator
- Only available in OPAL-t
- Can only model standard flat-pole undulators, rather than arbitrary fieldmaps
- No load balancing
- Many more particles required for full-wave solver than for FFT solver



Thank you to Andreas, Arya,
and all OPAL developers for
the help in developing this tool.

Thank you for your attention.
Questions?

References



Agostino Marinelli.

Introduction to the Physics of Free Electron Lasers, 2016.



Zhen Zhang, Joseph Duris, James P MacArthur, Alexander Zholents, Zhirong Huang, and Agostino Marinelli.

Experimental demonstration of enhanced self-amplified spontaneous emission by photocathode temporal shaping and self-compression in a magnetic wiggler.

New Journal of Physics, 22(8):083030, August 2020.



James P. MacArthur, Joseph Duris, Zhen Zhang, Alberto Lutman, Alexander Zholents, Xinlu Xu, Zhirong Huang, and Agostino Marinelli.

Phase-stable self-modulation of an electron-beam in a magnetic wiggler.

Physical Review Letters, 123(21):214801, November 2019.

arXiv: 1909.02166.



Arnau Albà.

Start-to-end modelling of the AWA microbunched electron cooling POP-experiment.

PhD thesis, ETHZ, PSI, Villigen, PSI, 2020.



Arya Fallahi, Alireza Yahaghi, and Franz X. Kärtner.

MITHRA 1.0: A full-wave simulation tool for free electron lasers.

Computer Physics Communications, 228:192–208, July 2018.



Arya Fallahi.

MITHRA 2.0: A Full-Wave Simulation Tool for Free Electron Lasers.

arXiv e-prints, 2009:arXiv:2009.13645, September 2020.



Arnau Albà, Andreas Adelman, and Arya Fallahi.

OPAL-MITHRA: Self-consistent Software for Start-to-End Simulation of Undulator-based Facilities.

In *2020 33rd International Vacuum Nanoelectronics Conference (IVNC)*, pages 1–2, Lyon, France, July 2020. IEEE.



G. Stupakov and P. Baxevanis.

Microbunched electron cooling with amplification cascades.

Physical Review Accelerators and Beams, 22(3):034401, March 2019.



Alexander Zholents.

Wiggler Impact on the Electron Beam Self Energy Modulation in View of Electron-Ion Collider R&D, August 2019.