

PAUL SCHERRER INSTITUT



Matthias Frey :: Paul Scherrer Institut

Cyclotron Simulations with OPAL

14 September 2020 :: OPAL Introduction

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

- **Wiki:**

- <https://gitlab.psi.ch/OPAL/src/-/wikis/home>

- Compile instructions
 - Available binaries for Linux and macOS
 - Examples
 - OPAL Mailing list subscription at
<https://psilists.ethz.ch/sympa/subscribe/opal>

- **Source Code:**

- `git clone https://gitlab.psi.ch/OPAL/src.git`

- **Manual:**

- <http://amas.web.psi.ch/opal/Documentation/master/index.html>

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

Assuming the OPAL executable is part of your \$PATH environment variable!

- **Single Core:** \$ opal [inputfile.in]

```

Ipp1> CommMPI: Parent process waiting for children ...
Ipp1> CommMPI: Initialization complete.
>
>
>      /  --- \ |  ---  \ / \   | |
>     | | | | | | | | | | | | | |
>     | | | | | | | | | | | | | |
>     | | | | | | | | | | | | | |
>     \ --- / | | / - - - \ | | | |
>
OPAL>
OPAL> This is OPAL (Object Oriented Parallel Accelerator Library) Version 2.4.0
OPAL>          git rev. 1fd20f79e78e1e3dbbdd21d12416b52d688120c1
OPAL>
OPAL>
OPAL>          (c) PSI, http://amas.web.psi.ch
OPAL>
...

```

Assuming the OPAL executable is part of your \$PATH environment variable!

- **Multiple Cores:** \$ mpirun -np [number of cores] opal [inputfile.in]

```

Ipp1> CommMPI: Parent process waiting for children ...
Ipp1> CommMPI: Started job 1 on host 'R2-D2'.
Ipp1> CommMPI: Started job 2 on host 'R2-D2'.
Ipp1> CommMPI: Started job 3 on host 'R2-D2'.
Ipp1> CommMPI: Child 2 ready.
Ipp1> CommMPI: Child 1 ready.
Ipp1> CommMPI: Child 3 ready.
Ipp1> CommMPI: Initialization complete.
{0}>
{0}>
{0}>
{0}>
{0}>
{0}>
{0}>
OPAL{0}>
OPAL{0}> This is OPAL (Object Oriented Parallel Accelerator Library) Version 2.1.0
OPAL{0}>          git rev. 88400b8ffdcba529ace97bd6f40d16c55d9e4ca8
OPAL{0}>
OPAL{0}>
OPAL{0}>
OPAL{0}>          (c) PSI, http://amas.web.psi.ch
OPAL{0}>
...

```

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools


```

Option, PSDUMPFREQ      = 10;      // H5 phase space dump
Option, SPTDUMPFREQ     = 10;      // single particle dump
Option, PSDUMPEACHTURN  = false;    // H5 turn dump
Option, STATDUMPFREQ    = 1;        // statistics dump
Option, VERSION=20400;   // OPAL 2.4.0
...

```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#sec.control.option>




Setup of Input File – Cyclotron Example

```

REAL Ekin    = 0.072;           // [GeV]
REAL gamma   = (Ekin+PMASS)/PMASS;
REAL beta    = sqrt(1-(1/gamma^2));
REAL gambet  = gamma*beta;
REAL P0      = gamma*beta*PMASS;

VALUE,{gamma,beta,gammabeta,Ekin}; // print values

```



Setup of Input File – Cyclotron Example


```

ring: CYCLOTRON, TYPE="RING", CYHARMON=6, PHIINIT=0.0,
      PRINIT=-0.000174, RINIT=2130.0,
      SYMMETRY=8.0, RFFREQ=frequency,
      FMAPFN="s03av.nar";

rf0: RFCAVITY, VOLT=volt1st, FMAPFN="Cav1.dat",
      TYPE="SINGLEGAP", FREQ=frequency,
      RMIN = 1900.0, RMAX = 4500.0,
      ANGLE=35.0, PDIS = 416.0,
      GAPWIDTH = 220.0, PHI0=phi01;


rf1: RFCAVITY, ...;
rf2: RFCAVITY, ...;
rf3: RFCAVITY, ...;
rf4: RFCAVITY, ...;

```



Setup of Input File – Cyclotron Example


```
l1: LINE = (ring, rf0, rf1, rf2, rf3, rf4);
```



```
Dist1: DISTRIBUTION, TYPE=GAUSS, SIGMAX = 2.0e-03,
      SIGMAPX = 1.0e-7,
      CORRX = 0.0,
      SIGMAY = 2.0e-03,
      SIGMAPY = 1.0e-7,
      CORRY = 0.0,
      SIGMAT = 2.0e-03,
      SIGMAPT = 3.394e-4,
      CORRT = 0.0;
```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.distribution>




```

Fs1: FIELDSOLVER, FSTYPE = FFT,    // Fourier solver
      MX          = 32,    // no. grid points
      MY          = 32,
      MT          = 16,
      PARFFTX    = true,  // parallelize?
      PARFFTY    = true,
      PARFFTT    = true,
      BCFFTX     = open, // boundary condition
      BCFFTY     = open,
      BCFFTZ     = open;

```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#sec.fieldsolvers.fieldsolvercmd>




```

beam1: BEAM, PARTICLE = PROTON ,
        PC           = P0 ,
        NPART        = 1e5 ,
        BCURRENT     = 1.0E-3 ,
        CHARGE       = 1.0 ,
        BFREQ        = frequency ;

```


Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.beam-command>



Setup of Input File – Cyclotron Example

```
SELECT, LINE = 11;
```



```

TRACK , LINE           = 11 ,
      BEAM              = beam1 ,
      MAXSTEPS          = nstep*turns ,
      STEPSPERTURN     = nstep ,
      TIMEINTEGRATOR   = "RK-4" ;

RUN , METHOD            = "CYCLOTRON-T" ,
      BEAM              = beam1 ,
      FIELDSOLVER      = Fs1 ,
      DISTRIBUTION     = Dist1 ;


ENDTRACK ;

STOP ;

```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.track>



```
Option, ECHO=FALSE;
Option, PSDUMPFREQ=60;
Option, SPTDUMPFREQ = 10;
Option, PSDUMPEACHTURN=false;
Option, REPARTFREQ=20;
Option, ECHO=FALSE;
Option, STATDUMPFREQ=1;
Option, CZERO=FALSE;
Option, TELL=TRUE;
Option, VERSION=20400;

Title,string="OPAL-cycl: the first 10 turns in PSI 590MeV Ring";

REAL Edes=.072;
REAL gamma=(Edes+PMASS)/PMASS;
REAL beta=sqrt(1-(1/gamma^2));
REAL gambet=gamma*beta;
REAL P0 = gamma*beta*PMASS;
REAL brho = (PMASS*1.0e9*gambet) / CLIGHT;

//value,{gamma,brho,Edes,beta,gambet};
```

```
REAL phi01=139.4281;
REAL phi02=phi01+180.0;
REAL phi04=phi01;
REAL phi05=phi01+180.0;
REAL phi03=phi01+10.0;

REAL volt1st=0.9;
REAL volt3rd=0.9*4.0*0.112;

REAL turns = 10;
REAL nstep=360;

REAL frequency=50.650;
REAL frequency3=3.0*frequency;

ring: Cyclotron, TYPE="RING", CYHARMON=6, PHIINIT=0.0,
      PRINIT=-0.000174, RINIT=2130.0, SYMMETRY=8.0, RFFREQ=frequency,
      FMAPFN="s03av.nar";

rf0: RFCavity, VOLT=volt1st, FMAPFN="Cav1.dat", TYPE="SINGLEGAP",
      FREQ=frequency, RMIN = 1900.0, RMAX = 4500.0, ANGLE=35.0, PDIS = 416.0,
      GAPWIDTH = 220.0, PHI0=phi01;
```

```
rf1: RFCavity, VOLT=volt1st, FMAPFN="Cav1.dat", TYPE="SINGLEGAP",  
    FREQ=frequency, RMIN = 1900.0, RMAX = 4500.0, ANGLE=125.0, PDIS = 416.0,  
    GAPWIDTH = 220.0, PHIO=phi02;  
  
rf2: RFCavity, VOLT=volt3rd, FMAPFN="Cav3.dat", TYPE="SINGLEGAP",  
    FREQ=frequency3, RMIN = 1900.0, RMAX = 4500.0, ANGLE=170.0, PDIS = 452.0,  
    GAPWIDTH = 250.0, PHIO=phi03;  
  
rf3: RFCavity, VOLT=volt1st, FMAPFN="Cav1.dat", TYPE="SINGLEGAP",  
    FREQ=frequency, RMIN = 1900.0, RMAX = 4500.0, ANGLE=215.0, PDIS = 416.0,  
    GAPWIDTH = 220.0, PHIO=phi04;  
  
rf4: RFCavity, VOLT=volt1st, FMAPFN="Cav1.dat", TYPE="SINGLEGAP",  
    FREQ=frequency, RMIN = 1900.0, RMAX = 4500.0, ANGLE=305.0, PDIS = 416.0,  
    GAPWIDTH = 220.0, PHIO=phi05;  
  
l1:   Line = (ring,rf0,rf1,rf2,rf3,rf4);
```

```
Dist1:DISTRIBUTION, TYPE=gauss,
  sigmax = 2.0e-03,
  sigmapx = 1.0e-7,
  corrx = 0.0,
  sigmay = 2.0e-03,
  sigmapy = 1.0e-7,
  corry = 0.0,
  sigmat = 2.0e-03,
  sigmapt = 3.394e-4,
  corrt=0.0;

Fs1:FIELDSOLVER, FSTYPE=FFT, MX=32, MY=32, MT=16,
  PARFFTX=true, PARFFTY=true, PARFFTT=true,
  BCFFTX=open, BCFFTY=open, BCFFTT=open, BBOXINCR=2;

beam1: BEAM, PARTICLE=PROTON, pc=P0, NPART=1e5, BCURRENT=1.0E-3, CHARGE=1.0, BFREQ= frequency;

Select, Line=11;

TRACK,LINE=11, BEAM=beam1, MAXSTEPS=nstep*turns, STEPSPERTURN=nstep,TIMEINTEGRATOR="RK-4";
  run, method = "CYCLOTRON-T", beam=beam1, fieldsolver=Fs1, distribution=Dist1;
endtrack;

Stop;
```

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

OPAL Units

A consistent set of units is still work in progress

Quantity	Dimension
Length	m (metres) & mm (OPAL-cycl)
Angle	rad (radians) & deg (OPAL-cycl)
Quadrupole coefficient	Tm^{-1}
Multipole coefficient, 2n poles	Tm^{-n+1}
Electric voltage	MV (Megavolts)
Electric field strength	MV/m
Frequency	MHz (Megahertz)
Particle energy	MeV or eV
Particle mass	MeV/c^2
Particle momentum	$\beta\gamma$ or eV
Beam current	A (Amperes)
Particle charge	e (elementary charges)
Impedances	$M\Omega$ (Megohms)
Emittances ¹	m rad
RF power	MW (Megawatts)

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#sec.conventions.units>

¹(normalized and geometric)

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

Running OPAL with the input file `inputfile.in` generates following output files:

- `inputfile.h5`
File storing full particle phase space data; also used for restarts
- `inputfile.stat`
Bunch statistics stored in SDDS format
- `inputfile-trackOrbit.dat`
Orbit of reference particle and particle with small deviation from reference orbit
- `inputfile-afterEachTurn.dat`
Phase space data in global cylindrical coordinates after each turn; single particle mode only
- `inputfile-Angle{0,1,2}.dat`
Phase space data at azimuth $\theta = 0, \frac{\pi}{8}, \frac{\pi}{4}$ in global cylindrical coordinates; single particle mode only
- `inputfile.lbal`
Load-balancing of particles among MPI ranks

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations



Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools



Charles Darwin (Wikipedia)

²Y. Ineichen, Toward massively parallel multi-objective optimisation with application to particle accelerators. Diss. ETH No. 21114 (2013)

```
dv1: DVAR, VARIABLE="varname", // variable name
      LOWERBOUND=0.1, // lower bound
      UPPERBOUND=0.2; // upper bound
```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.optimiser>

optimizer.in

set options

declare constants

define DVAR

define OBJECTIVE

define CONSTRAINT

define OPTIMIZE

²Y. Ineichen, Toward massively parallel multi-objective optimisation with application to particle accelerators. Diss. ETH No. 21114 (2013)

```
obj1: OBJECTIVE ,  Expr="expression";
```

Example:

```
drmsx: OBJECTIVE ,  
      Expr="fabs(statVariableAt('rms_x', 2.0))";
```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.optimiser>

optimizer.in

set options

declare constants

define DVAR

define OBJECTIVE

define CONSTRAINT

define OPTIMIZE

²Y. Ineichen, Toward massively parallel multi-objective optimisation with application to particle accelerators. Diss. ETH No. 21114 (2013)

```
con1: CONSTRAINT,  Expr="expression";
```

Example:

```
crmsx: CONSTRAINT,  
      Expr="statVariableAt('rms_x', 1.0) < 0.003";
```

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.optimiser>

optimizer.in

set options

declare constants

define DVAR

define OBJECTIVE

define CONSTRAINT

define OPTIMIZE

²Y. Ineichen, Toward massively parallel multi-objective optimisation with application to particle accelerators. Diss. ETH No. 21114 (2013)

```

OPTIMIZE, INPUT="inputfile.tpl",
OBJECTIVES      = {obj1, obj2, ...},
DVARs           = {dv1, dv2, ...},
INITIALPOPULATION = 5,
MAXGENERATIONS  = 10,
NUM_IND_GEN     = 5,
MUTATION_PROBABILITY = 0.43,
SIMBIN_CROSSOVER_NU = 2.0,
NUM_MASTERS     = 1,
NUM_COWORKERS   = 2,
SIMTMPDIR       = "simtmpdir", // simulation directory
TEMPLATEDIR     = "template", // directory of inputfile.tpl
FIELDMAPDIR     = "fieldmaps",
OUTPUT          = "outname",
OUTDIR          = "results",
KEEP            = {STAT, IN, H5}; // do not delete

```

optimizer.in

set options

declare constants

define DVAR

define OBJECTIVE

define CONSTRAINT

define OPTIMIZE

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.optimiser>

²Y. Ineichen, Toward massively parallel multi-objective optimisation with application to particle accelerators. Diss. ETH No. 21114 (2013)

- A template file is like an input file.
- **But:** All design variables need to be defined in the template file.
- **Example:**
optimizer.in

```
dv1: DVAR, VARIABLE="bcurrent", // beam current
      LOWERBOUND=0.001, // [A]
      UPPERBOUND=0.002; // [A]
```

inputfile.tmpl


```
beam1: BEAM, PARTICLE = PROTON,
        PC           = P0,
        NPART        = 1e5,
        BCURRENT     = .bcurrent_,
        CHARGE        = 1.0,
        BFREQ         = frequency;
```

- A **JSON**³ file **per generation**
- A **JSON** file with **pareto front** individuals

```
{
  "name": "opt-pilot",
  "OPAL version": "2.3.0",
  "git revision": "7f506bf9abbe51f800e5cc5c5d991712adbc59bb",
  "dvar-bounds": {
    "sigmax": "[ 0.002, 0.0022 ]"
  },
  "constraints": "",
  "population": {
    "1": {
      "obj": {
        "GOALFUN": "0.0019817400858543012"
      },
      "dvar": {
        "sigmax": "0.0020306983200833201"
      }
    }
  },
  ...
}
```

³JavaScript Object Notation

Pareto Front?



(Taken from <https://gitlab.psi.ch/OPAL/opt-pilot/wikis/optpilot-week>)

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer

OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

```
sm1: SAMPLING, VARIABLE = "varname",
      TYPE             = "UNIFORM",
      SEED              = 42,
      N                  = 100;      // number of samples
```

TYPE = FROMFILE, GAUSSIAN, ...

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.sampler>

sampler.in

set options

declare constants

define DVAR

define OBJECTIVE

define SAMPLING

define SAMPLE

```

SAMPLE, RASTER           = false,
INPUT                    = "inputfile.tpl",
SAMPLINGS                = {sm1, sm1, ...},
DVARs                    = {dv1, dv2, ...},
OBJECTIVES               = {obj1, obj2, ...},
NUM_MASTERS              = 1,
NUM_COWORKERS            = 2,
SIMTMPDIR                = "simtmpdir", // simulation directory
TEMPLATEDIR              = "template", // directory of inputfile.tpl
FIELDMAPDIR              = "fieldmaps",
OUTPUT                   = "outname",
OUTDIR                   = "results",
KEEP                     = {STAT, IN, H5}; // keep only

```

sampler.in

set options

declare constants

define DVAR

define OBJECTIVE

define SAMPLING

define SAMPLE

Manual:

<http://amas.web.psi.ch/opal/Documentation/master/index.html#chp.sampler>

- A JSON file **per master**

```
{  
  "name": "sampler",  
  "OPAL version": "2.4.0",  
  "git revision": "1fd20f79e78e1e3dbbdd21d12416b52d688120c1",  
  "dvar-bounds": {  
    "numparticles": "[ 4096, 8192 ]"  
  },  
  "samples": {  
    "0": {  
      "dvar": {  
        "numparticles": "4096"  
      },  
      "obj": {  
        "OBJ1": "0.00083601928199118259"  
      }  
    },  
    "1": {  
      "dvar": {  
        "numparticles": "4551"  
      },  
      "obj": {  
        "OBJ1": "0.00083433398855364176"  
      }  
    },  
    ...  
  },  
  ...  
}
```

General Information

How to run OPAL?

Setup of Input File for Cyclotron Simulations

Units

OPAL Output Files

OPAL-Optimizer


OPAL-Sampler

Data Postprocessing & Visualization with pyOPALTools

- Website: <https://gitlab.psi.ch/OPAL/pyOPALTools>
- Checkout: `git clone https://gitlab.psi.ch/OPAL/pyOPALTools.git`
(developers: `git clone git@gitlab.psi.ch:OPAL/pyOPALTools.git`)
- Under development – contributors are welcome!

January 12, 2017 – April 11, 2020

Commits to master, excluding merge commits. Limited to 6,000 commits.



pyOPALTools

Search docs

- amr package
- db package
- jobhandler package
- opal package
- optPilot package
- pc package
- setup module
- surrogate package

amas.web.psi.ch/docs/pyOPALTools/surrogate.html

Docs » pyOPALTools Documentation

[View page source](#)

pyOPALTools Documentation

pyOPALTools

- [amr package](#)
 - [Submodules](#)
 - [amr.AmrOpal module](#)
- [db package](#)
 - [Submodules](#)
 - [db.mldb module](#)
- [jobhandler package](#)
 - [Submodules](#)
 - [jobhandler.submit module](#)
- [opal package](#)
 - [Subpackages](#)
 - [opal.analysis package](#)
 - [Submodules](#)
 - [opal.analysis.H5Statistics module](#)
 - [opal.analysis.OptimizerAnalysis module](#)

Data Loading

```
from opal import load_dataset, filetype

# load a specific file (here HDF5) using its file name
ds = load_dataset(directory='/path/to/files/',
                  fname='filename.h5')

# show summary of dataset
print(ds)

# load files using their file type (here HDF5)
dsets = load_dataset(directory='/path/to/files/',
                    filetype=filetype.H5)
```

Data Access

```
# obtain array of positions of macroparticles in x-direction at step 1  
x_data = ds.getData(var='x', step=1)  
  
# unit of positions  
x_unit = ds.getUnit(var='x')  
  
# variable name, mainly used as axis labels  
x_label = ds.getLabel(var='x')
```

file type	format	description
AMR	HyperCLaw-V1.1 ⁴	particle phase space and AMR grid data
GRID	SDDS	AMR load balancing
HIST	ASCII	histogram of the radial positions of the particles at probe elements
H5	HDF5	particle phase space, used as a check point file
LBAL	SDDS	load balancing of macroparticles
LOSS	ASCII	phase space data of particles lost at elements (e.g., collimator, stripper)
MEM	SDDS	virtual memory consumption
OPTIMIZER	JSON	generation files and Pareto file of multiobjective genetic algorithm
OUTPUT	ASCII	OPAL standard output
PEAK	ASCII	peak values of the histogram generated by a radial probe
SAMPLER	JSON	all individual simulations of a sample run
SMB	SDDS	statistical measures of individual bunches of a neighboring bunch model
SOLVER	SDDS	AMR multigrid solver convergence information
STAT	SDDS	statistical measures of the bunch
TIMING	ASCII	runtime of individual code sections
TRACK_ORBIT	ASCII	single particle phase space data

⁴A file format of AMReX.


Data Plotting

```
# set the plotting style
from opal.visualization.styles import load_style

load_style('jupyter') # 'default' or 'poster'


# load the dataset
from opal.opal import load_dataset
ds = load_dataset('.', fname='RingCyclotron.stat')

# create plot
import matplotlib.pyplot as plt
plt.figure(figsize=(9, 4))
plt = ds.plot_profile1D('time', 'rms_x', xsci=True)
plt.grid(linestyle='dashed')
plt.tight_layout()
plt.show()
```



Data Plotting


```
# load the dataset  
ds = load_dataset('.', fname='RingCyclotron.h5')  
  
# create plot  
plt = ds.plot_phase_space('x', 'px', step=5)  
plt.show()
```



Data Plotting

```
# load the dataset
ds = load_dataset('.', fname='RingCyclotron-trackOrbit.dat')

# create plot
plt = ds.plot_orbits(linewidth=0.5)
plt.gca().set_aspect('equal')
plt.grid(linestyle='dashed')
plt.show()
```



Thanks to
OPAL developer team

